

## Rubinate M, Suprasec 5005, A-Side Component

**SECTION 1. IDENTIFICATION**

Product name : Rubinate M, Suprasec 5005, A-Side Component

**Manufacturer or supplier's details**

Company name of supplier : Huntsman Building Solutions  
Address : 3315 E Division St  
Arlington, TX 76011  
United States of America (USA)  
Telephone : Tech Info:(817) 460-4900

E-mail address of person responsible for the SDS : info@huntsmanbuilds.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

**Recommended use of the chemical and restrictions on use**

Recommended use : Component of a Polyurethane System.

Restrictions on use : For industrial use only.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Acute toxicity (Inhalation) : Category 4  
Skin irritation : Category 2  
Eye irritation : Category 2B  
Respiratory sensitisation : Category 1  
Skin sensitisation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

**GHS label elements**

Hazard pictograms : 

Signal word : Danger

Hazard statements : H315 + H320 Causes skin and eye irritation.  
H317 May cause an allergic skin reaction.

## Rubinate M, Suprasec 5005, A-Side Component

Print Date 08/03/2021

H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.

## Precautionary statements

: **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves.  
 P285 In case of inadequate ventilation wear respiratory protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337 + P313 If eye irritation persists: Get medical advice/attention.  
 P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
 P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

**Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Diphenylmethanediisocyanate	9016-87-9	50 - 70
4,4'-methylenediphenyl diisocyanate	101-68-8	30 - 50

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

## Rubinate M, Suprasec 5005, A-Side Component

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Do not leave the victim unattended.  
Get medical attention immediately if symptoms occur.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : If breathed in, move person into fresh air.  
Call a physician or poison control centre immediately.  
Keep patient warm and at rest.  
Keep respiratory tract clear.  
If breathing is difficult, give oxygen.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.  
Consult a physician immediately if symptoms such as shortness of breath or asthma are observed.  
A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons.  
The exposed person may need to be kept under medical surveillance for 48 hours.  
LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.
- Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Take off contaminated clothing and shoes immediately.  
Wash contaminated clothing before reuse.  
Thoroughly clean shoes before reuse.  
Call a physician if irritation develops or persists.  
An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be more effective than soap and water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
Seek medical advice.

## Rubinate M, Suprasec 5005, A-Side Component

- If swallowed : Gently wipe or rinse the inside of the mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Keep respiratory tract clear. Keep at rest. If a person vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious person. Take victim immediately to hospital. If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Severe allergic skin reactions, bronchospasm and anaphylactic shock  
 This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation.  
 Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing.  
 The onset of the respiratory symptoms may be delayed for several hours after exposure.  
 A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.  
 It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.  
 If potential for exposure exists refer to Section 8 for specific personal protective equipment.  
 First Aid responders should pay attention to self-protection and use the recommended protective clothing
- Notes to physician : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.  
 The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry powder
- Unsuitable extinguishing media : Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.

**Rubinate M, Suprasec 5005, A-Side Component**

Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses. The pressure in sealed containers can increase under the influence of heat. Exposure to decomposition products may be a hazard to health.
Hazardous combustion products	: Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.
Specific extinguishing methods	: Cool containers/tanks with water spray.
Further information	: Standard procedure for chemical fires. Due to reaction with water producing CO <sub>2</sub> -gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Prevent fire extinguishing water from contaminating surface water or the ground water system. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	: Immediately evacuate personnel to safe areas. Use personal protective equipment. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Only qualified personnel equipped with suitable protective equipment may intervene. For additional precautions and advice on safe handling, see section 7. Never return spills in original containers for re-use. Make sure that there is a sufficient amount of neutralizing/absorbent material near the storage area. The danger areas must be delimited and identified using relevant warning and safety signs. Treat recovered material as described in the section "Disposal considerations". For disposal considerations see section 13.
Environmental precautions	: Do not allow uncontrolled discharge of product into the environment. Do not allow material to contaminate ground water system. Prevent product from entering drains.

## Rubinate M, Suprasec 5005, A-Side Component

Prevent further leakage or spillage if safe to do so.  
 Local authorities should be advised if significant spillages cannot be contained.  
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Clean-up methods - small spillage  
 Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
 Clean contaminated surface thoroughly.  
 Sweep up or vacuum up spillage and collect in suitable container for disposal.  
 Neutralize small spillages with decontaminant.  
 The compositions of liquid decontaminants are given in Section 16.  
 Remove and dispose of residues.  
 Clean-up methods - large spillage  
 If the product is in its solid form:  
 Spilled MDI flakes should be picked up carefully.  
 The area should be vacuum cleaned to remove remaining dust particles completely.  
 If the product is in its liquid form:  
 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Leave to react for at least 30 minutes.  
 Shovel into open-top drums for further decontamination.  
 Wash the spillage area with water.  
 Test atmosphere for MDI vapour.  
 Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Use only with adequate ventilation.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.  
 Avoid formation of aerosol.  
 Do not breathe vapours or spray mist.  
 Do not breathe vapours/dust.  
 Do not swallow.  
 Do not get in eyes or mouth or on skin.  
 Do not get on skin or clothing.  
 Avoid exposure - obtain special instructions before use.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Keep container closed when not in use.  
 Open drum carefully as content may be under pressure.

## Rubinate M, Suprasec 5005, A-Side Component

Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)

- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
Observe label precautions.  
Protect from moisture.  
Electrical installations / working materials must comply with the technological safety standards.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.
- Further information on storage stability : Stable under recommended storage conditions.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA Z-1

#### Personal protective equipment

- Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
In emergency, non-routine and unknown exposure situations, including confined space entries, a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied air respirator (SAR) with auxiliary self-contained air supply, should be used.

## Rubinate M, Suprasec 5005, A-Side Component

## Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include: Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene\*), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton\*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

When only brief contact is expected, a glove with protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN374) is recommended.  
Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier  
By industrial use of aprotic polar solvents for cleaning : Butyl rubber (0.7mm), Nitrile rubber (0.4mm), Chloroprene (0.5mm)

## Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.  
Chemical splash goggles.  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.  
Ensure that eyewash stations and safety showers are close to the workstation location.

## Skin and body protection

: Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Recommended:  
Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek Pro 'F' disposable coverall.

## Protective measures

: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing



## Rubinate M, Suprasec 5005, A-Side Component

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Ensure that eye flushing systems and safety showers are located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 When using do not eat, drink or smoke.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Wash hands before breaks and immediately after handling the product.  
 Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : brown, Clear

Odour : slight, musty

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : > 302 °F / > 150 °C  
 Method: closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : < 0.00001 hPa (68 °F / 20 °C)

Relative vapour density : No data is available on the product itself.

**Rubinate M, Suprasec 5005, A-Side Component**

Relative density	: 1.23
Density	: 1.23 g/cm <sup>3</sup> (77 °F / 25 °C) Method: estimated
Solubility(ies)	
Water solubility	: Decomposes in contact with water. (68 °F / 20 °C) Method: Information given is based on data obtained from similar substances.
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Thermal decomposition	: No data is available on the product itself.
Self-Accelerating decomposition temperature (SADT)	: No data is available on the product itself.
Viscosity	
Viscosity, dynamic	: 200 mPa.s (77 °F / 25 °C)
Explosive properties	: No data is available on the product itself.
Oxidizing properties	: No data is available on the product itself.
Particle size	: No data is available on the product itself.

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reaction with water (moisture) produces CO <sub>2</sub> -gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.
Conditions to avoid	: Extremes of temperature and direct sunlight. Exposure to air or moisture over prolonged periods.
Incompatible materials	: Acids

## Rubinate M, Suprasec 5005, A-Side Component

Amines  
Bases  
Metals  
water

Hazardous decomposition products : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : No data is available on the product itself.

**Acute toxicity**

Acute oral toxicity - Product : LD50 (Rat, male): > 10,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity - Product : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute toxicity estimate: 1.36 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Remarks: Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.

Acute dermal toxicity - Product : LD50 (Rabbit, male and female): > 9,400 mg/kg  
Method: OECD Test Guideline 402

Acute toxicity (other routes of administration) : No data available

**Skin corrosion/irritation****Components:**

Diphenylmethanediisocyanate:  
Species: Rabbit  
Assessment: Irritating to skin.  
Method: OECD Test Guideline 404

## Rubinate M, Suprasec 5005, A-Side Component

Result: Skin irritation

4,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

**Serious eye damage/eye irritation****Components:**

Diphenylmethanediisocyanate:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

4,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Result: Mild eye irritation

**Respiratory or skin sensitisation****Components:**

Diphenylmethanediisocyanate:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Exposure routes: Respiratory Tract

Species: Rat

Result: May cause sensitisation by inhalation.

4,4'-methylenediphenyl diisocyanate:

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

Exposure routes: Respiratory Tract

Species: Guinea pig

Result: May cause sensitisation by inhalation.

Assessment:

May cause an allergic skin reaction., May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

: Concentration: 200 ug/plate

Metabolic activation: with and without metabolic activation

Method: Directive 67/548/EEC, Annex, B.13/14

Result: negative

**Product:**

## Rubinate M, Suprasec 5005, A-Side Component

Genotoxicity in vivo : Application Route: Inhalation  
Result: Not classified due to inconclusive data.

Application Route: Inhalation  
Exposure time: 3 Weeks  
Dose: 113 mg/m<sup>3</sup>  
Method: OECD Test Guideline 474  
Result: negative

**Product:**

Germ cell mutagenicity-  
Assessment : Tests on bacterial or mammalian cell cultures did not show  
mutagenic effects.

**Carcinogenicity****Product:**

Remarks: Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in a chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m<sup>3</sup>), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m<sup>3</sup> and no effects at 0.2 mg/m<sup>3</sup>. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

Remarks: Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)  
Based on animal studies, primary aromatic amines are considered as potential carcinogen to humans. Some of those chemicals are proven carcinogens to humans  
Provided the recommended personal protective equipment and hygiene measures are applied, no adverse effects to human health are to be expected

Species: Rat, male and female  
Application Route: Inhalation  
Exposure time: 24 month(s)  
Dose: 1 mg/m<sup>3</sup>  
Frequency of Treatment: 5 daily  
Method: OECD Test Guideline 453  
Result: positive

Species: Rat, male and female  
Application Route: Inhalation  
Exposure time: 24 month(s)  
Dose: 1 mg/m<sup>3</sup>  
Frequency of Treatment: 5 daily  
Method: OECD Test Guideline 453  
Result: positive

Carcinogenicity -  
Assessment : No data available

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

## Rubinate M, Suprasec 5005, A-Side Component

human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Product:**

Effects on fertility

: Species: Rat, male and female  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Remarks: No significant adverse effects were reported

**Product:**

Effects on foetal development

: Species: Rat, male and female  
Application Route: Inhalation  
General Toxicity Maternal: 4 mg/m<sup>3</sup>  
Method: OECD Test Guideline 414  
Result: No teratogenic effects

**Product:**

Reproductive toxicity - Assessment

: No toxicity to reproduction  
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

**STOT - single exposure****Product:**

Exposure routes: Inhalation  
Target Organs: Respiratory Tract  
Assessment: May cause respiratory irritation.

**STOT - repeated exposure****Product:**

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.  
Remarks: Lung decrement has been reported in some studies as a consequence of repeated exposure to MDI. However, this effect can only be observed after inhalation exposure in the tissue at the point of contact and does not represent systemic toxicity. It is a local effect that is already covered by respiratory irritation (STOT single exposure, Cat. 3) and respiratory sensitization (Category 1).

In some humans, but not all, epidemiological studies have found long term decreases in ventilatory function and respiratory symptoms (EU RA 2005). However, there is generally co-exposure to other materials and sometimes also to toluene diisocyanate which may have

## Rubinate M, Suprasec 5005, A-Side Component

contributed to lung decrement. Therefore, it is concluded that possible lung effects do not qualify as specific target organ toxicity after repeated exposure in accordance to chapter 3.9.1.6 of the GHS (UNECE 2003). In addition, all warning and safety measures for local effects as well as for acute inhalation toxicity already provide for a protection of workers and professional users that are involved in the handling of MDI.

**Repeated dose toxicity****Product:**

Species: Rat, male and female  
NOEC: 0.2 mg/m<sup>3</sup>  
Exposure time: 17,520 h  
Number of exposures: 5 d  
Method: OECD Test Guideline 453

Repeated dose toxicity - Assessment : No data available

**Aspiration toxicity**

No data available

**Experience with human exposure**

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

**Toxicology, Metabolism, Distribution**

No data available

**Neurological effects**

No data available

**Further information**

Ingestion: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

Toxicity to fish - Product : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
Exposure time: 96 h

## Rubinate M, Suprasec 5005, A-Side Component

---

	Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 203
	LC0: > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates - Product	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants - Product	: EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	: No data available
Toxicity to fish (Chronic toxicity)	: No data available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) - Product	: NOEC (Daphnia magna (Water flea)): >= 10 mg/l Exposure time: 21 d Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	: No data available
Toxicity to microorganisms - Product	: EC50 (activated sludge): > 100 mg/l Exposure time: 3 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 209
Toxicity to soil dwelling organisms - Product	: EC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg Exposure time: 336 h Method: OECD Test Guideline 207
Plant toxicity	: No data available
Sediment toxicity	: No data available
Toxicity to terrestrial organisms	: No data available
Ecotoxicology Assessment Acute aquatic toxicity	: No data available



## Rubinate M, Suprasec 5005, A-Side Component

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

**Persistence and degradability**

Biodegradability - Product : Inoculum: Domestic sewage  
Concentration: 30 mg/l  
Result: Not biodegradable  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: Inherent Biodegradability: Modified MITI Test (II)

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

**Components:**

Diphenylmethanediisocyanate:  
Stability in water : Degradation half life(DT50): 0.8 d (77 °F / 25 °C)  
Method: No information available.  
Remarks: Fresh water

4,4'-methylenediphenyl diisocyanate:  
Stability in water : Degradation half life(DT50): 20 hrs (77 °F / 25 °C)  
Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

**Bioaccumulative potential**

Bioaccumulation - Product : Species: Cyprinus carpio (Carp)  
Bioconcentration factor (BCF): 200  
Remarks: Bioaccumulation is unlikely.

## Rubinate M, Suprasec 5005, A-Side Component

**Components:**

4,4'-methylenediphenyl diisocyanate:

Partition coefficient: n- : log Pow: 4.51 (68 °F / 20 °C)  
octanol/water pH: 7  
Method: OECD Test Guideline 117**Mobility in soil**

Mobility : No data available

Distribution among : No data available  
environmental compartments

Stability in soil : No data available

**Other adverse effects**Environmental fate and : No data available  
pathwaysResults of PBT and vPvB : No data available  
assessmentEndocrine disrupting : No data available  
potentialAdsorbed organic bound : No data available  
halogens (AOX)**Hazardous to the ozone layer**Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).Additional ecological : No data available  
informationGlobal warming potential : No data available  
(GWP)**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.

## Rubinate M, Suprasec 5005, A-Side Component

Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA

Not regulated as dangerous goods

##### IMDG

Not regulated as dangerous goods

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### DOT Classification

UN/ID/NA number : NA 3082  
 Proper shipping name : OTHER REGULATED SUBSTANCES, LIQUID, N.O.S.  
 (Methylene Diphenyl Diisocyanate)  
 Class : 9  
 Packing group : III  
 Labels : Class 9 - Miscellaneous dangerous substances and articles  
 ERG Code : 171  
 Marine pollutant : no

##### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
4,4'-methylenediphenyl diisocyanate	101-68-8	5000	11904
chlorobenzene	108-90-7	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Respiratory or skin sensitisation  
 Specific target organ toxicity (single or repeated exposure)

## Rubinate M, Suprasec 5005, A-Side Component

<b>SARA 313</b>	:	The following components are subject to reporting levels established by SARA Title III, Section 313:		
		Diphenylmethanediisocyanate	9016-87-9	>= 50 - < 70 %
		4,4'-methylenediphenyl diisocyanate	101-68-8	>= 30 - < 50 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

4,4'-methylenediphenyl diisocyanate	101-68-8
-------------------------------------	----------

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

CH INV	:	On the inventory, or in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
AICS	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	On the inventory, or in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**TSCA - 5(a) Significant New Use Rule List of Chemicals**

No substances are subject to a Significant New Use Rule.

**US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)**


No substances are subject to TSCA 12(b) export notification requirements.

## Rubinate M, Suprasec 5005, A-Side Component

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : \*- sodium carbonate : 5 - 10 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 2 : \*- concentrated ammonia solution : 3 - 8 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Revision Date : 11/19/2019

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / C	: Ceiling

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

## Rubinate M, Suprasec 5005, A-Side Component

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.