

HUNTSMAN

BUILDING SOLUTIONS

Discover the performance characteristics of Huntsman Building Solutions Classic Ultra Select™

- Low VOC formulation
- Eliminates the requirement for an ignition barrier in residential unvented attic applications
- Start spraying with drum temperatures as low as 70°F
- Consistent high yield & improved sprayability



CLASSIC ULTRA SELECT™

OPEN-CELL SPRAY FOAM



CLASSIC ULTRA SELECT™

OPEN-CELL SPRAY FOAM



PRODUCT FEATURES

- Core Density: 0.5 lb/ft³
- R-Value: R-3.7 per 1"
- Air Barrier at 3"
- Can be sprayed in a wide temperature range for applications, making it suitable for any climate
- No ignition barrier required for limited-access attic and crawlspace applications
- Low VOC allowing for re-entry after 1 hour, and re-occupancy after 4 hours (at 20ACH)
- No pre-spray paddle mixing by hand.

Huntsman Building Solutions Draw Mixer does all the work ensuring a thorough mix and optimizing pre-spray preparation time.

THICKNESS (inches)	R-VALUE (°F•ft ² •h/Btu)
1	R-3.7
3.5	R-13
4	R-14
5.5	R-20
7	R-25
10	R-36
11.5	R-41

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your energy savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your energy use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on energy. To get the marked R-value, it is essential that this insulation be installed properly.

