

HUNTSMAN

BUILDING SOLUTIONS

**IGNITION
BARRIER
FREE FOR
UNVENTILATED
ATTICS**



SEALECTION[®] 500

OPEN-CELL SPRAY FOAM



SEALECTION® 500
OPEN-CELL SPRAY FOAM



CUTS ENERGY COSTS UP TO 50%*

Sealection® 500 is an easily applied, open-cell spray foam that provides an efficient lifelong building envelope. It is an industry-leading spray foam formula that expands 120 times its liquid volume to insulate and seal all cracks, gaps and joints with a single application. Sealection 500 is easy to install and finish, and has now been tested and certified for use in unventilated attics without a prescribed ignition barrier.

For more information, consult CCRR-1063 on the Huntsman Building Solutions website.

PRODUCT FEATURES

- Ignition barrier free for unventilated attics
- Maintains performance throughout time and temperature
- Allows the use of smaller HVAC systems
- Minimizes outside noise
- Reduces dust and allergens

R-value	3.81 @ 1 inch
Density	1/2 lb/ft ³

*Aged R-value at 4 inches per ASTM C518



Complies with the International Building Code® (IBC), the International Residential Code® (IRC), and the International Energy Conservation Code® (IECC).

*Source: HBS analysis report of a side-by-side comparison of two identical homes built by Habitat for Humanity; one installed with traditional fiberglass insulation by an anonymous donor, and one installed with HBS Sealection 500 spray foam insulation donated to Habitat for Humanity.